



669.00 EUR  
incl. 19% VAT, plus [shipping](#)

**New from September 2011:**

- New panel type (Higher contrast)
- Metal- instead of plastic-enclosure

The CTF-1210 TFT-Display is equipped with a 12.1" TFT panel and comes with many nice features. In any case it is the ideal display- and input-unit for your Laptop, CarPC or HTPC. Because of the 4:3 aspect ratio and the size of 12.1", the display is perfectly suitable for being used in POS-section or on boats. With the touchscreen functionality you easily can control your PC. The brilliant VGA-display ensures a maximum readability and sharpness.

The CTF-1210 can be used with any PC/MAC with VGA- and USB port.

Driver-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

| Specifications        |                               |
|-----------------------|-------------------------------|
| Display size          | 12.1" digital                 |
| Aspect ratio          | 4:3 wide TFT screen           |
| Dot Resolution        | 2400x600= 1,440,000 dots      |
| Physical Resolution   | 800x600                       |
| Supported Resolutions | 640x480-1900x1200             |
| Color configuration   | RGB stripe                    |
| Power input           | DC 12VDC                      |
| Power consumption     | max. 45W                      |
| Video system          | 1x Video input RCA (PAL/NTSC) |
|                       | 1x Video input S-Video        |
|                       | 1x VGA input                  |

|                              |                                                                  |
|------------------------------|------------------------------------------------------------------|
| <i>Dimensions</i>            | Display Case : 310mm x 220mm x 20mm<br>Display : 246mm x 184.5mm |
| <i>Video input signal</i>    | 1.0Vp-p, composite video                                         |
| <i>Brightness</i>            | 400 cd/m²                                                        |
| <i>Contrast</i>              | 600:1                                                            |
| <i>Vibration</i>             | IEC68-2-6                                                        |
| <i>Operating Temperature</i> | -30° bis 85°C                                                    |
| <i>Features</i>              | Full function OSD control (englisch)                             |
|                              | VESA-mounting holes (75mm)                                       |
| <i>Scope of supply</i>       | - 12.1" VGA Touchscreen TFT with Video-support                   |
|                              | - Mounting unit                                                  |
|                              | - VGA-connector cable                                            |
|                              | - Power supply f. 110/230V Steckdose                             |
|                              | - Cigarette Lighter Adapter                                      |
|                              | - USB-connector cable                                            |
|                              | - Touchscreen Driver-CD                                          |
|                              | - Manual                                                         |