



729.00 EUR

incl. 19% VAT, plus [shipping](#)

- INTEL® LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- INTEL® Q170 Express Chipset
- SO-DIMM DDR3L 1333/1066MHz \* 2 (Max 16GB)
- Giga LAN Port \* 8
- Support HDMI \* 1, GPIO \* 1 (optional)
- Support COM Port \* 1 (RJ-45 type)
- Support USB 2.0 Port \* 2, USB 3.0 Port \* 2
- Power Source ■ 1U 200W FLEX POWER, AC 90~240V input
- Applications ■ Networking, Surveillance

|                   |                                                                                                                                  |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Product Dimension | 430 (W) * 251 (D) * 43 (H) mm                                                                                                    |
| Product Model     | JBC150F592-Q170-B                                                                                                                |
| MB Model & Size   | JNF592-Q170 / MINI-ITX                                                                                                           |
| BIOS              | AMI 128MB SMT Flash ROM                                                                                                          |
| CPU               | Intel® LGA 1151 Socket Core i7/i5/i3/Pentium Processor                                                                           |
| Memory            | SO-DIMM DDR3L 1333/1066MHz * 2 (Max 16GB)                                                                                        |
| Storage           | 2.5" SATA HDD * 2 (Support RAID-1) or 3.5" SATA HDD * 1                                                                          |
| Expansion         | Full size Mini-PCIE * 1<br>SIM Card Slot * 1<br>Support TPM (optional)                                                           |
| FAN               | DC-12V / 4020 FAN * 3                                                                                                            |
| Front I/O Port    | Power LED * 1, HDD LED * 1<br>PW-SW * 1, RESET SW * 1<br>USB 2.0 * 2                                                             |
| Rear I/O Port     | AC input * 1<br>PW SW * 1 & RESET SW * 1<br>Giga LAN * 8<br>USB 3.0 * 2<br>HDMI * 1, GPIO * 1 (optional)<br>COM * 1 (RJ-45 type) |
| Power Source      | 1U 200W FLEX POWER<br>AC 90~240V input                                                                                           |
| Accessory         | AC Cable * 1, Screw Package * 1<br>User Manual * 1, CD * 1                                                                       |
| Packing           | Net Weight ■ 4.2KG<br>Gross Weight ■ 5KG<br>Color Box Dimension ■ 560 (W) x 400 (D) x 380 (H) mm                                 |
| Temperature       | Operating Temperature : 0°C~50°C<br>Storage Temperature : -10°C~70°C                                                             |

---

|                 |                                |
|-----------------|--------------------------------|
| • Certification | • CE, FCC, RoHS, ErP           |
| • Applications  | • Networking<br>• Surveillance |