

198.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Pico-ITX
- SATA
- DDR-II !
- 1 Ghz CPU



|               |                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------|
| Model         | VIA EPIA PX10000G                                                                                |
| Processor     | VIA C7 1.0 GHz - Socket NanoBGA2                                                                 |
| Chipset       | VIA VX700 Unified Digital Media GCP Chipset                                                      |
| System Memory | 1 DDR2 512 SDRAM socket<br>Up to 1GB memory size                                                 |
| GPU           | Integrated VIA UniChrome Pro 3 3D2D AGP graphics<br>with MPEG-2/4 and WMV9 decoding acceleration |

|                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Onboard IDE             | 1 UltraDMA 133/100/66 connector (2 Drive 64 pin header)                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Onboard Serial ATA      | 1 SATA connector                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Onboard LAN             | 1 VIA VT6105G 10/100Mbps Ethernet controller<br><br>with Power Management System                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Onboard Audio           | VIA VT1708A High Definition Audio Codec                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Internal I/O Connectors | <p>4 USB pin headers for 4 USB 2.0 ports</p> <ul style="list-style-type: none"> <li>• 1 COM port connector</li> <li>• 1 PS2 mouse/keyboard pin header</li> <li>• 1 LVDS/DVI connector</li> <li>• 1 Multimedia connector to support external TV-out interface, Video capture port interface and Low pin count interface</li> <li>• 1 Audio pin header for line-out, line-in, mic-in, S/PDIF in, and 7.1 channels audio output</li> <li>• 1 Fan pin header for CPU fan</li> <li>• 1 Pico-ITX power connector</li> </ul> |
| External I/O Ports      | <p>1 RJ-45 LAN port</p> <ul style="list-style-type: none"> <li>• 1 VGA port</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                |
| BIOS                    | <p>Award BIOS</p> <ul style="list-style-type: none"> <li>• 4/8Mbit flash memory</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Management              | <p>CPU temperature reading (manufacturing option)</p> <ul style="list-style-type: none"> <li>• Watch Dog Timer (manufacturing option)</li> <li>• Keyboard-Power-on, Timer-Power-on</li> <li>• Wake-on-LAN</li> <li>• System power management</li> <li>• AC power failure recovery</li> </ul>                                                                                                                                                                                                                          |
| Operating Temperature   | 0°C ~ 50°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Operating Humidity      | 20% ~ 90% (relative humidity, non-condensing)                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Form Factor             | <ul style="list-style-type: none"> <li>• Pico-ITX 10 cm x 7.2 cm</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                           |